



Niton XL2: With point-and-shoot simplicity, you can view the alloy grade and chemistry on the built-in, color, touch-screen display.

The Niton XL2 stands far above the competition, with its many standard features and available options. By utilizing the standard Thermo Scientific Niton Data Transfer (NDT[®]) PC software suite to customize the instrument, you can set operator permissions, generate custom reports, print certificates of analysis personalized with your own company logo, or remotely monitor and operate the instrument hands-free from your PC. Integrated USB and Bluetooth[®] communications provide direct data transfer to your PC or networked storage device, eliminating the cumbersome data synchronization procedures required by Windows Mobile[®]-based XRF analyzers.

Niton XL2 Analyzers

Whether you need an analyzer for metal alloy analysis, mining operations, or electronics and consumer goods screening, the value choice Niton XL2 provides cost-effective high-speed performance, point-and-shoot simplicity, and the cutting-edge technology that you have come to expect from industry-leading Thermo Scientific Niton XRF analyzers.

Thermo Scientific Niton XL2 Specifications	
Weight	3 lbs 5.8 oz (1.53 kg)
Dimensions	10.25 x 11 x 4 in. (256 x 275 x 100 mm)
Tube	Ag anode 45 kV maximum, 80 uA maximum
Detector	High-performance semiconductor
System Electronics	400 MHz ARM 11 CPU 300 MHz dedicated DSP 80 MHz ASICS DSP for signal processing 4096 channel MCA 64 MB internal system memory/128 MB internal user storage
Display	Fixed angle, color, touch-screen display
Standard Analytical Range	>25 elements from S to U (varies by application)
Data Storage	Internal >10,000 readings with spectra
Data Transfer	USB, Bluetooth [™] , and RS-232 serial communication
Security	Password-protected user security
Mode (Varies by application)	Alloy Modes: Metal Alloy, Electronics Alloy, Precious Metals Bulk Modes: Mining, Soil Plastic Modes: RoHS Plastics, Toy & Consumer Goods Plastics, TestAll [™] , Painted Products
Data Entry	Touch-screen keyboard User-programmable pick lists Optional wireless remote barcode reader
Standard Accessories	Integrated camera Locking shielded carrying case Shielded belt holster Two 6-cell lithium-ion battery packs 110/220 VAC battery charger/ AC adaptor PC connection cables (USB and RS-232) Niton Data Transfer (NDT) PC software Safety lanyard Check samples/standards
Optional Features and Accessories	Engine Guard protects critical detection components and minimizes operational downtime Thermo Scientific portable test stand, stationary (bench-top) stand, mobile test stand Welding mask Soil testing guard
Licensing/Registration	Varies by region. Contact your local distributor.
Compliance	CE, RoHS

Thermo Scientific Niton XL2 analyzers represent just one of our handheld analyzer solutions, which include XRF tools for metal alloy identification, lead-based paint testing, RCRA metals in soil, toy and consumer goods screening, RoHS and WEEE compliance screening, and many other analysis needs.



Thermo Fisher Scientific,
San Jose, CA USA is ISO Certified.

thermoscientific.com/niton

Bluetooth is a registered trademark of Bluetooth SIG. Windows Mobile is a registered trademark of Microsoft Corporation.

© 2015 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Africa-Other +27 11 570 1840
Australia +61 2 8844 9500
Austria +43 1 333 50 34 0
Belgium +32 53 73 42 41
Canada +1 800 530 8447
China +86 10 8419 3588
Denmark +45 70 23 62 60
Europe-Other +43 1 333 50 34 0

Finland /Norway/Sweden
+46 8 556 468 00
France +33 1 60 92 48 00
Germany +49 6103 408 1014
India +91 22 6742 9434
Italy +39 02 950 591
Japan +81 45 453 9100
Latin America +1 608 276 5659

Middle East +43 1 333 50 34 0
Netherlands +31 76 579 55 55
South Africa +27 11 570 1840
Spain +34 914 845 965
Switzerland +41 61 716 77 00
UK +44 1442 233555
USA +1 800 532 4752

Thermo
SCIENTIFIC

A Thermo Fisher Scientific Brand